

3000

Meyer® Insulation Blowing Machine Model 300-2B




SINCE 1930

SERIES

*Insulation Blowing Technology
for Professionals by Professionals*





Meyer® Insulation Blowing Machine M

Insulation Blower- and Sprayer Systems by Meyer® - Technology with o

Product benefits at a glance:

- Solid technology
- Simple and quick assembly
- High performance motors
- Variable speed blower
- Simple adjustment of material quantity
- Fill quantity adjustment through rotary air lock
- Tested quality
- CE-certified
- Convenient dimensions




Set-up requires only a few steps



Connect to power source



Manual material adjustment through sieve and slide gate



Performance gauge



Remote control



Start blowing material

Sophisticated solid technology for professionals

Meyer®'s Insulation Blowing Machine Series 300-2B introduced here is a modern and compact blower for cellulose insulation material. It is particularly useful for those professional companies intending to insulate their own construction sites in a fast and economical manner. But its durable technology and simple operation as well as its low

maintenance requirements make the M300 also the perfect partner for the professional insulation applicator. Applicators also appreciate the simple mechanical protection- and relay technology, which allows the expert to service the machine on site - machine downtimes are therefore reduced to a minimum.

Two 1.0 kW blowers ensure an economical performance, a positive compaction of insulation materials as well as a settlement-free processing. More than seven decades of experience in the production of insulation blowing systems is your assurance that this technology is the right choice.







Technical specifications


Machine specifications

Series 300-2B

Processing capacity (max. theoretical processing capacity)	800 kg
Control cable	60 m
Drive motor	1.56 kW/h
Blower	2 x 1.0 kW/h 0.30 bar 190 m ³ /h
Rotary air lock	24 x 24 cm
Weight (w/o accessories)	180 kg
Dimensions (W x L x H)	660 mm x 970 mm x 1,220 mm
Schlauchanschluss	3"

Optional accessories

Hose Sizes 2", 2.5", 3"	Connectors For various hose sizes	Clamps To securely connect the hoses
		
Intake pipe (Cleaning at construction site)	Suction blower (Cleaning at construction site)	Sprayer set With connection to water supply
		



Meyer® Sales Europe

Insulation Blower- and Sprayer Systems by Meyer® - Technology with optimum performance



Sales: **MEYER MASCHINEN EUROPE**
Dipl. Ing.(FH) Martin Weise
Wiehenweg 6, 32130 Enger - Germany
Tel.: +49(0)5224-997840
Fax.: +49(0)5224-997841
Mob.: +49(0)151-12659602
e-mail: weise-m@t-online.de

Sales partner: